NSN 5962-00-758-7829

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-758-7829
Body Length:
Between 0.240 inches and 0.275 inches
Body Width:
Between 0.160 inches and 0.185 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
30.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+200.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and medium speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
8 input
Design Function And Quantity:
1 gate, nand
Case Outline Source And Designator:
T0-85 joint electron device engineering council
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 24.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
13499-351-7081 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Fiig: A458a0

Yes - demil/mli