NSN 5962-00-759-6782

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-759-6782

| Body Length: |
|--|
| Between 0.355 inches and 0.395 inches |
| Body Width: |
| Between 0.230 inches and 0.270 inches |
| Body Height: |
| 0.075 inches |
| Maximum Power Dissipation Rating: |
| 0.5 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+125.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and w/open collector and negative outputs and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 9 input |
| Design Function And Quantity: |
| 1 driver |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| -1.5 volts power source and 5.5 volts power source |
| Precious Material And Location: |
| Terminal surface gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 26512-123scpe5200 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 14 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization: Yes - demil/mli

NSN 5962-00-759-6782Digital Microcircuit - Page 2 of 2



Fiig:

A458a0