# NSN 5962-00-759-6971

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-759-6971

# **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

# **Body Height:**

Between 0.165 inches and 0.185 inches

# Maximum Power Dissipation Rating:

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **Features Provided:**

Hermetically sealed and monolithic and internally compensated and negative outputs and positive outputs

# **Inclosure Material:**

Glass and metal

Inclosure Configuration:

# Can

Input Circuit Pattern:

4 input

# **Design Function And Quantity:**

1 amplifier, operational, general purpose

# Case Outline Source And Designator:

T0-78 joint electron device engineering council

# **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-15.0 volts power source and 15.0 volts power source

# **Test Data Document:**

26512-ga811bu1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0