

View Online at <https://aerobasegroup.com/nsn/5962-00-760-2170>

**Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and internally compensated and low power and high gain and negative outputs and positive outputs

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

2 input

**Design Function And Quantity:**

1 amplifier, operational, general purpose

**Case Outline Source And Designator:**

T0-99 joint electron device engineering council

**Terminal Surface Treatment:**

Gold

**Time Rating Per Characteristic:**

300.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminal surface gold

**Precious Material:**

Gold

**Test Data Document:**

49956-480805 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0