## NSN 5962-00-760-2291

Digital Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-00-760-2291   |
|---|
| Body Length:  |
| Between 0.660 inches and 0.785 inches   |
| Body Width:   |
| Between 0.220 inches and 0.280 inches   |
| Body Height:  |
| Between 0.140 inches and 0.180 inches   |
| Maximum Power Dissipation Rating:   |
| 132.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and monolithic and high speed and positive outputs  |
| Inclosure Material:   |
| Ceramic and glass   |
| Inclosure Configuration:  |
| Dual-in-line  |
| Output Logic Form:  |
| Transistor-transistor logic   |
| Input Circuit Pattern:  |
| Hex 1 input   |
| Design Function And Quantity:   |
| 6 inverter, digital   |
| Case Outline Source And Designator:   |
| T0-116 joint electron device engineering council  |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| -1.5 volts power source and 5.5 volts power source  |
| Time Rating Per Chacteristic:   |
| 6.00 nanoseconds propagation delay time, low to high level output and 6.00 nanoseconds propagation delay time, high to low level output |
| Terminal Type And Quantity:   |
| 14 printed circuit  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |

Fiig:

A458a0