NSN 5962-00-762-0615

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-762-0615
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
900.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Darlington-connected and monolithic and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Dual-in-line Input Circuit Pattern:
Input Circuit Pattern:
Input Circuit Pattern: 6 input
Input Circuit Pattern: 6 input Design Function And Quantity:
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator:
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment:
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity:
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 14 printed circuit
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life:
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a
Input Circuit Pattern: 6 input Design Function And Quantity: 2 amplifier, differential Case Outline Source And Designator: T0-116 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:

A458a0