## NSN 5962-00-764-1844

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-764-1844

| View Online at https://aerobasegroup.com/nsn/5962-00-764-1844  |
|--|
| Body Length:   |
| Between 0.660 inches and 0.785 inches  |
| Body Width:  |
| Between 0.220 inches and 0.280 inches  |
| Body Height:   |
| Between 0.140 inches and 0.180 inches  |
| Maximum Power Dissipation Rating:  |
| 176.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and positive outputs and high speed and w/totem pole output                                     |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| Dual 4 input   |
| Design Function And Quantity:  |
| 2 gate, and  |
| Case Outline Source And Designator:  |
| T0-116 joint electron device engineering council   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| -1.5 volts power source and 5.0 volts power source   |
| Time Rating Per Chacteristic:  |
| 15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level |
| output   |
| Terminal Type And Quantity:  |
| 14 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| Yes - demil/mli  |

Fiig:

A458a0