NSN 5962-00-776-0067

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-776-0067

Body Length:

Between 0.240 inches and 0.275 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

570.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

Dual 4 input

Design Function And Quantity:

2 receiver, line

Case Outline Source And Designator:

T0-86 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Chacteristic:

100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

37695-619293 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0