## NSN 5962-00-782-5067

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-782-5067

**Body Length:** 

Between 0.330 inches and 0.350 inches

**Body Width:** 

Between 0.240 inches and 0.260 inches

**Body Height:** 

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:** 

28.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**End Application:** 

Interrogator set type an/apx-7 (v) and an/apx-76a(v)

**Features Provided:** 

Hermetically sealed and monolithic and positive outputs and low power

**Inclosure Material:** 

Ceramic and glass

**Inclosure Configuration:** 

Flat pack

**Output Logic Form:** 

Transistor-transistor logic

**Input Circuit Pattern:** 

Quad 2 input

**Criticality Code Justification:** 

Feat

**Design Function And Quantity:** 

4 gate, nand

**Case Outline Source And Designator:** 

T0-88 joint electron device engineering council

**Terminal Surface Treatment:** 

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Chacteristic:** 

27.00 nanoseconds propagation delay time, low to high level output

**Special Features:** 

Weapon system essential

**Terminal Type And Quantity:** 

14 flat leads

Shelf Life:

N/a

## NSN 5962-00-782-5067

Digital Microcircuit - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0