## **NSN 5962-00-816-5531**Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-816-5531
Body Length:
Between 0.240 inches and 0.275 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
0.070 inches
Maximum Power Dissipation Rating:
34.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and medium speed and medium power and positive outputs
Inclosure Material:
Ceramic and metal
Inclosure Configuration:
Flat pack
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 gate, nand
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
04660-77c800 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5962-00-816-5531

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0