NSN 5962-00-816-8807

Digital Microcircuit - Page 1 of 1

Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-00-816-8807 **Body Length:** 0.350 inches **Body Width:** 0.260 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and w/enable and presettable and w/clear and complementary outputs and edge triggered **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 flip-flop, j-k, clocked **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Special Features:** Formed leads; package bottom insulated **Test Data Document:** 94580-1996489 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:**