NSN 5962-00-828-6890

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-00-828-6890 |
|--|
| Body Outside Diameter: |
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 200.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and negative outputs and positive outputs |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 4 channel |
| Design Function And Quantity: |
| 2 switch, analog |
| Case Outline Source And Designator: |
| T0-100 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -20.0 volts power source and 10.0 volts power source |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 10 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0