

View Online at <https://aerobasegroup.com/nsn/5962-00-861-3215>

**Body Length:**

Between 0.240 inches and 0.260 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

0.060 inches

**Maximum Power Dissipation Rating:**

40.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and medium speed and positive outputs and expandable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Diode-transistor logic

**Input Circuit Pattern:**

Dual 5 input

**Design Function And Quantity:**

2 gate, nand-nor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

**Time Rating Per Characteristic:**

80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

12464-b77t0028 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0