NSN 5962-00-865-4594Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-865-4594
Body Length:
Between 0.240 inches and 0.275 inches
Body Width:
Between 0.125 inches and 0.260 inches
Body Height:
Between 0.035 inches and 0.070 inches
Maximum Power Dissipation Rating:
35.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and complementary outputs and w/enable
Inclosure Material:
Ceramic or metal
Inclosure Configuration:
Flat pack
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 multivibrator, monostable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
24384-200445 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A458a0

Yes - demil/mli