NSN 5962-00-872-4050

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-872-4050

| Body Length: |
|---|
| Between 0.240 inches and 0.275 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.030 inches and 0.070 inches |
| Maximum Power Dissipation Rating: |
| 34.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and low power and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Diode-transistor logic |
| Input Circuit Pattern: |
| Dual 4 input |
| Design Function And Quantity: |
| 2 expander |
| Case Outline Source And Designator: |
| T0-86 joint electron device engineering council |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| -1.5 volts power source and 5.5 volts power source |
| Precious Material And Location: |
| Terminal surface gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 14 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| _ |
| Demilitarization: |

Yes - demil/mli

NSN 5962-00-872-4050

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0