

View Online at <https://aerobasegroup.com/nsn/5962-00-882-9335>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

250.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and low power and positive outputs and medium speed

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Output Logic Form:

Resistor-transistor logic

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 gate, nand-nor

Case Outline Source And Designator:

T0-99 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

4.0 volts power source

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

99971-7528158 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0