NSN 5962-00-897-7371

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-897-7371

| Body Outside Diameter: |
|--|
| Between 0.335 inches and 0.370 inches |
| Body Height: |
| Between 0.165 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and high gain and negative outputs and positive outputs |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 4 input |
| Case Outline Source And Designator: |
| T0-99 joint electron device engineering council |
| Terminal Surface Treatment: |
| Tin |
| Test Data Document: |
| 28009-16600102-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |
| |