NSN 5962-00-901-7466

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-901-7466 **Body Length:** Between 0.245 inches and 0.280 inches **Body Width:** Between 0.245 inches and 0.280 inches **Body Height:** 0.065 inches **Maximum Power Dissipation Rating:** 40.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Expandable and hermetically sealed and monolithic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode-transistor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, nand-nor **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 6.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 49671-8504076 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-00-901-7466Digital Microcircuit - Page 2 of 2



Fiig:

A458a0