NSN 5962-00-904-2545Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-904-2545
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.145 inches and 0.185 inches
Maximum Power Dissipation Rating:
27.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and negative outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Output Logic Form:
Direct-coupled-transistor logic
Input Circuit Pattern:
4 input
Design Function And Quantity:
1 gate
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
4.0 volts power source
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
10001-2558145 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A458a0