NSN 5962-00-916-6337

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-916-6337 **Overall Height:** 0.685 inches **Body Outside Diameter:** Between 0.335 inches and 0.370 inches **Body Height:** Between 0.165 inches and 0.185 inches **Maximum Power Dissipation Rating:** 250.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and positive outputs and hermetically sealed **Inclosure Material:** Metal **Inclosure Configuration:** Can **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 gate **Case Outline Source And Designator:** To-5 joint electron device engineering council **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 14.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 13499-351-7026 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 8 pin Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-00-916-6337Digital Microcircuit - Page 2 of 2



Fiig:

A458a0