NSN 5962-00-922-2968

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-922-2968 **Body Length:** 0.265 inches **Body Width:** 0.265 inches **Body Height:** 0.065 inches **Maximum Power Dissipation Rating:** 52.0 milliwatts **Operating Tempurature Range:** +0.0/+100.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and w/resistor and positive outputs and low impedance **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 buffer and 1 driver, inverting **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 12.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 94117-1310002 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:**

Fiig: A458a0

Demilitarization: Yes - demil/mli