

View Online at <https://aerobasegroup.com/nsn/5962-00-925-5647>

**Body Length:**

Between 0.240 inches and 0.290 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:**

30.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Diode-transistor logic

**Input Circuit Pattern:**

3 input

**Design Function And Quantity:**

1 gate, nand-nor and 1 gate, power

**Case Outline Source And Designator:**

T0-91 joint electron device engineering council

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

40.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminal surface gold

**Precious Material:**

Gold

**Test Data Document:**

04655-32-268353 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0