

View Online at <https://aerobasegroup.com/nsn/5962-00-934-3445>

**Body Length:**

Between 0.750 inches and 0.785 inches

**Body Width:**

Between 0.240 inches and 0.280 inches

**Body Height:**

0.200 inches

**Maximum Power Dissipation Rating:**

62.5 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Diode-transistor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nand-nor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

8.0 volts power source

**Time Rating Per Characteristic:**

80.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

45413-134198 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0