

View Online at <https://aerobasegroup.com/nsn/5962-00-936-9286>

Body Length:

0.640 inches

Body Width:

0.640 inches

Body Height:

0.115 inches

Maximum Power Dissipation Rating:

625.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-55.0/+200.0 degrees celsius

Features Provided:

Hybrid and hermetically sealed and negative outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

1 input

Design Function And Quantity:

1 translator, level

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 23.0 volts power source

Time Rating Per Characteristic:

1500.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output

Special Features:

Formed leads

Precious Material:

Gold

Test Data Document:

06481-972163 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0