NSN 5962-00-945-7970

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-945-7970

| view offilite at https://aerobasegroup.com/hsh/5502-00-545-7570 |
|--|
| Body Length: |
| Between 0.240 inches and 0.290 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.030 inches and 0.070 inches |
| Maximum Power Dissipation Rating: |
| 63.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Emitter-coupled logic |
| Input Circuit Pattern: |
| 5 input |
| Design Function And Quantity: |
| 1 translator, level |
| Case Outline Source And Designator: |
| T0-91 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 6.0 volts power source |
| Time Rating Per Chacteristic: |
| 35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level |
| output |
| Terminal Type And Quantity: |
| 10 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0