# NSN 5962-00-947-0549

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-947-0549

# **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

# **Body Height:**

Between 0.165 inches and 0.185 inches

# Maximum Power Dissipation Rating:

500.0 milliwatts

# **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **Features Provided:**

Monolithic and hermetically sealed and medium power and positive outputs and medium speed

#### **Inclosure Material:**

Glass and metal

Inclosure Configuration:

Can

#### **Output Logic Form:**

Resistor-transistor logic

#### Input Circuit Pattern:

2 input

# **Design Function And Quantity:**

1 buffer, inverting

# Case Outline Source And Designator:

T0-99 joint electron device engineering council

# **Time Rating Per Chacteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

# **Precious Material And Location:**

Terminal surface gold

# Precious Material:

Gold

# Test Data Document:

15786-84630 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

```
Shelf Life:
```

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0