NSN 5962-00-993-0060



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-00-993-0060 **Body Length:** 0.265 inches **Body Width:** 0.265 inches **Body Height:** Between 0.030 inches and 0.080 inches **Maximum Power Dissipation Rating:** 160.0 milliwatts **Operating Tempurature Range:** +0.0/+75.0 degrees celsius Storage Tempurature Range: -65.0/+200.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and expandable and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 wide 3-2-2-3 input **Design Function And Quantity:** 4 gate, and-or **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 5.00 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output **Precious Material:** Gold **Test Data Document:** 05869-717310 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-00-993-0060Digital Microcircuit - Page 2 of 2



Fiig:

A458a0