NSN 5962-01-004-9400

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-004-9400

| View Offiline at https://derobasegroup.com/risin/5902-01-004-5400 |
|--|
| Overall Height: |
| Between 0.280 inches and 0.350 inches |
| Body Length: |
| Between 0.745 inches and 0.785 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.135 inches and 0.150 inches |
| Maximum Power Dissipation Rating: |
| 760.0 milliwatts |
| Operating Tempurature Range: |
| -40.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and w/resistor |
| Inclosure Material: |
| Ceramic or plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 7 input |
| Design Function And Quantity: |
| 1 amplifier, general purpose |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Integrated circuit, am receiver subsystem and general purpose amplifier array |
| Voltage Rating And Type Per Characteristic: |
| 16.0 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0