NSN 5962-01-005-0725



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-005-0725 **Body Length:** 0.980 inches **Body Width:** Between 0.995 inches and 1.095 inches **Body Height:** 0.190 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+75.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and negative outputs and positive outputs and medium speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 switch, ladder, digital to analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -15.0 volts power source and 5.0 volts power source **Time Rating Per Chacteristic:** 1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 10001-2994376 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 30 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0