NSN 5962-01-005-5120

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-005-5120

Body Length:

Between 0.240 inches and 0.290 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.030 inches and 0.070 inches

Maximum Power Dissipation Rating:

240.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Aircraft type ftf-15a

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and internally compensated

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

6 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Case Outline Source And Designator:

T0-91 joint electron device engineering council

Terminal Surface Treatment:

Tin

Voltage Rating And Type Per Characteristic:

-8.0 volts power source and 8.0 volts power source

Time Rating Per Chacteristic:

150.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

03640-6088570 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

10 flat leads

Shelf Life:

N/a

Unit Of Measure:

- --
- Demilitarization:
- Yes demil/mli

NSN 5962-01-005-5120

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

