

View Online at <https://aerobasegroup.com/nsn/5962-01-005-6569>

Body Length:

0.730 inches

Body Width:

0.280 inches

Body Height:

0.165 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hybrid and hermetically sealed and negative outputs and positive outputs and high speed and w/field effect transistor switch and w/enable

Inclosure Material:

Glass and metal

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

2 channel

Design Function And Quantity:

2 switch, analog and 2 switch, field effect transistor

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-15.0 volts power source and 15.0 volts power source

Time Rating Per Characteristic:

1000.00 nanoseconds propagation delay time, low to high level output and 2500.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0