NSN 5962-01-005-9326

Digital Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5962-01-005-9326
Body Length:
Between 0.371 inches and 0.409 inches
Body Width:
Between 0.247 inches and 0.283 inches
Body Height:
Between 0.050 inches and 0.075 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs
nclosure Material:
Ceramic
nclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
nput Circuit Pattern:
10 input
Design Function And Quantity:
4 gate, nor
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
0.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
10.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level
putput
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
35351-151613 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a

Yes - demil/mli

Unit Of Measure:

Demilitarization:

NSN 5962-01-005-9326

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0