NSN 5962-01-005-9491

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-005-9491 **Body Length:** 0.785 inches **Body Width:** 0.265 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs and w/strobe **Inclosure Material:** Glass and metal **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 comparator, voltage **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source **Time Rating Per Chacteristic:** 200.00 nanoseconds propagation delay time, low to high level output **Precious Material And Location:** Terminals gold and body gold **Precious Material:** Gold **Test Data Document:** 30003-434as114 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-01-005-9491

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0