# NSN 5962-01-005-9492

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-005-9492

### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

### **Body Height:**

Between 0.165 inches and 0.185 inches

# **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and high speed

#### **Inclosure Material:**

Glass and metal

#### **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

2 input

# **Design Function And Quantity:**

1 comparator, voltage, differential

# **Case Outline Source And Designator:**

T0-99 joint electron device engineering council

# **Terminal Surface Treatment:**

Gold

### Voltage Rating And Type Per Characteristic:

-7.0 volts power source and 7.0 volts power source

#### **Time Rating Per Chacteristic:**

40.00 nanoseconds propagation delay time, low to high level output

### **Precious Material And Location:**

Terminals gold

#### **Precious Material:**

Gold

# **Test Data Document:**

13499-351-7189 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Terminal Type And Quantity:**

8 pin

Shelf Life:

N/a

#### Unit Of Measure:

- ---
- **Demilitarization:**
- Yes demil/mli

# NSN 5962-01-005-9492

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

