## NSN 5962-01-008-5975

Digital Microcircuit - Page 1 of 1

**Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-008-5975 **Body Length:** Between 0.800 inches and 0.840 inches **Body Width:** Between 0.235 inches and 0.290 inches **Body Height:** Between 0.135 inches and 0.150 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and w/buffered output and w/decoded output and w/storage and w/open collector **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Time Rating Per Chacteristic:** 400.00 nanoseconds propagation delay time, low to high level output and 400.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 50927-1dts1061 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a