## NSN 5962-01-009-2117

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-01-000-2117

View Online at https://aerobasegroup.com/nsn/5962-01-009-2117
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
1000.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and negative outputs and w/strobe
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 comparator, voltage, differential
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Tin
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
13973-862309 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0