

View Online at <https://aerobasegroup.com/nsn/5962-01-009-2138>

**Body Length:**

Between 0.660 inches and 0.785 inches

**Body Width:**

Between 0.220 inches and 0.280 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+150.0 degrees celsius

**Storage Temperature Range:**

-65.0/+200.0 degrees celsius

**Features Provided:**

Monolithic and hermetically sealed and high speed and positive outputs and asynchronous and synchronous and w/enable and presettable and resettable and negative edge triggered

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Design Function And Quantity:**

1 flip-flop, clocked and 1 flip-flop, j-k, and input

**Case Outline Source And Designator:**

U0-116 joint electron device engineering council

**Time Rating Per Characteristic:**

15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

13973-862709 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0