NSN 5962-01-009-7688

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5962-01-009-7666
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-40.0/+100.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and w/strobe and negative outputs and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
6 input
Design Function And Quantity:
2 amplifier, sense
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Tin
Time Rating Per Chacteristic:
70.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
13973-862301 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A458a0