NSN 5962-01-009-7688

Linear Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/hsn/5962-01-009-7666 |
|---|
| Body Length: |
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 500.0 milliwatts |
| Operating Tempurature Range: |
| -40.0/+100.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and w/strobe and negative outputs and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 6 input |
| Design Function And Quantity: |
| 2 amplifier, sense |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Terminal Surface Treatment: |
| Tin |
| Time Rating Per Chacteristic: |
| 70.00 nanoseconds propagation delay time, low to high level output |
| Test Data Document: |
| 13973-862301 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A458a0