## NSN 5962-01-010-3946

Digital Microcircuit - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-010-3946

Body Length:
0.385 inches
Body Width:
0.270 inches
Body Height:
Between 0.049 inches and 0.090 inches
Maximum Power Dissipation Rating:
10.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and electrostatic sensitive and w/resistor
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nand
Current Rating Per Characteristic:
1.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 8.0 volts power source
Time Rating Per Chacteristic:
60.00 nanoseconds propagation delay time, high to low level output and 60.00 nanoseconds propagation delay time, low to high level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

## NSN 5962-01-010-3946

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0