

View Online at <https://aerobasegroup.com/nsn/5962-01-010-7813>

Body Length:

Between 0.750 inches and 0.795 inches

Body Width:

Between 0.245 inches and 0.300 inches

Body Height:

Between 0.120 inches and 0.195 inches

Maximum Power Dissipation Rating:

385.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and high speed and schottky and w/decoded output and w/enable and w/strobe and w/totem pole output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 6 input

Design Function And Quantity:

2 multiplexer, four to one line

Case Outline Source And Designator:

-0-001-ag joint electron device engineering council

Time Rating Per Characteristic:

18.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0