# NSN 5962-01-010-7818

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-010-7818

# **Body Length:**

Between 0.350 inches and 0.390 inches

# **Body Width:**

Between 0.240 inches and 0.270 inches

# **Body Height:**

Between 0.034 inches and 0.044 inches

## **Maximum Power Dissipation Rating:**

1000.0 milliwatts

## **Operating Tempurature Range:**

-20.0/+95.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and programmable and programmed and w/enable and

w/storage

Inclosure Material:

Ceramic and metal

## Inclosure Configuration:

Flat pack

## Output Logic Form:

P-type metal oxide-semiconductor logic

## Input Circuit Pattern:

10 input

## **Time Rating Per Chacteristic:**

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

## **Precious Material And Location:**

Terminals gold

# **Precious Material:**

Gold

## **Test Data Document:**

13973-861553 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0