## NSN 5962-01-011-3274



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-011-3274 **Body Length:** Between 1.242 inches and 1.262 inches **Body Width:** Between 0.680 inches and 0.700 inches **Body Height:** Between 0.260 inches and 0.340 inches **Maximum Power Dissipation Rating:** 32.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and high power and high voltage **Inclosure Material:** Glass and metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 regulator, voltage **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 60.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level

50.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

31550-507384 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

4 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0