

View Online at <https://aerobasegroup.com/nsn/5962-01-011-9048>

**Body Length:**

Between 0.660 inches and 0.785 inches

**Body Width:**

Between 0.220 inches and 0.295 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

1000.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

C-2a (reprocured), b-2 bomber aircraft. Virginia class cgn (41), nimitz class cvn, kidd class ddg, arleigh burke class ddg, los angeles class ssn (688), spruance class dd (963), ticonderoga class cg (47).

**Features Provided:**

Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and adjustable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

4 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

2 regulator, voltage

**Case Outline Source And Designator:**

T0-116 joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

30.0 volts power source

**Special Features:**

Weapon system essential

**Test Data Document:**

07187-4018818 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0