NSN 5962-01-012-4470

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-012-4470 **Body Length:** Between 0.815 inches and 0.840 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.120 inches and 0.160 inches **Maximum Power Dissipation Rating:** 50.0 milliwatts **Operating Tempurature Range:** -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and medium speed and retriggerable and low power and resettable and complementary outputs and edge triggered **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Dual 3 input **Design Function And Quantity:** 2 multivibrator, monostable **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.5 volts power source **Time Rating Per Chacteristic:** 700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A458a0