# NSN 5962-01-013-8546

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-013-8546

Bodv	l er	nath:
Douv	LCI	ıuıı.

Between 0.350 inches and 0.390 inches

**Body Width:** 

Between 0.240 inches and 0.270 inches

**Body Height:** 

Between 0.034 inches and 0.044 inches

**Maximum Power Dissipation Rating:** 

1000.0 milliwatts

#### **Operating Tempurature Range:**

-20.0/+95.0 degrees celsius

#### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and negative outputs and positive outputs and programmable and programmed and w/enable and w/storage

#### **Inclosure Material:**

Ceramic and metal

# **Inclosure Configuration:**

Flat pack

# **Output Logic Form:**

P-type metal oxide-semiconductor logic

#### **Input Circuit Pattern:**

10 input

#### **Terminal Surface Treatment:**

Gold

# **Voltage Rating And Type Per Characteristic:**

-30.0 volts power source

#### **Time Rating Per Chacteristic:**

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

# **Memory Device Type:**

Rom

# **Memory Capacity:**

Unknown

#### **Precious Material And Location:**

Terminals gold

#### **Precious Material:**

Gold

# **Test Data Document:**

13973-861553 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Terminal Type And Quantity:**

24 flat leads

# Shelf Life:

. . .

# NSN 5962-01-013-8546

Memory Microcircuit - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0