# NSN 5962-01-014-1557

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-014-1557

## **Body Length:**

Between 0.750 inches and 0.770 inches

# **Body Width:**

Between 0.260 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.160 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-55.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and hermetically sealed and positive outputs and bipolar and programmable and programmed and w/open collector and w/enable and w/disable and w/buffered output and w/decoded output and expandable and wire-or outputs

## Inclosure Material:

Ceramic and glass

#### **Inclosure Configuration:**

Dual-in-line

## **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

10 input

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.5 volts power source

## **Time Rating Per Chacteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

## Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

16 printed circuit

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

# Fiig:

A458a0