## NSN 5962-01-014-4739

Digital Microcircuit - Page 1 of 1

Solder

output

14 flat leads

Shelf Life:

**Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

N/a

**Fiig:** A458a0

5.5 volts power source

**Test Data Document:** 

**Time Rating Per Chacteristic:** 

**Terminal Type And Quantity:** 

Voltage Rating And Type Per Characteristic:



View Online at https://aerobasegroup.com/nsn/5962-01-014-4739 **Body Length:** Between 0.337 inches and 0.350 inches **Body Width:** Between 0.235 inches and 0.265 inches **Body Height:** Between 0.050 inches and 0.080 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and positive outputs and w/strobe and w/totem pole output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, nor **Terminal Surface Treatment:** 

22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).