# NSN 5962-01-014-4742

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-014-4742

## **Body Length:**

Between 0.337 inches and 0.350 inches

## Body Width:

Between 0.235 inches and 0.265 inches

## **Body Height:**

Between 0.050 inches and 0.080 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and positive outputs and w/totem pole output

#### **Inclosure Material:**

Ceramic and glass

## Inclosure Configuration:

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

Hex 1 input

## **Design Function And Quantity:**

6 inverter

## **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

5.5 volts power source

# Time Rating Per Chacteristic:

22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

# Test Data Document:

96906-mil-std-883 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

14 flat leads

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

## Fiig:

A458a0