NSN 5962-01-014-9623

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-014-9623 **Body Length:** Between 0.240 inches and 0.280 inches **Body Width:** Between 0.240 inches and 0.270 inches **Body Height:** Between 0.030 inches and 0.070 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and w/field effect transistor switch **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 6 channel **Design Function And Quantity:** 6 driver, switch, field effect transistor **Terminal Surface Treatment:** Tin Voltage Rating And Type Per Characteristic: 30.0 volts power source **Time Rating Per Chacteristic:** 1200.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli